

SHORT LOOP CAPPELS



GENERAL DATA

ROPE DIAMETER		SAFE WORKING LOAD SF = 10:1		APPROXIMATE WEIGHT	
mm	in	kgf	tonf	mm	in
26	1	6096	6	20	44
29	1 1/8	6604	6 1/2	23	51
32	1 1/4	6604	6 1/2	29	64
35	1 3/8	7620	7 1/2	38	84
38	1 1/2	8128	8	46	102
41	1 5/8	9652	9 1/2	53	117
45	1 3/4	10668	10 1/2	68	150
48	1 7/8	12192	12	84	155
51	2	14732	14 1/2	109	240
54	2 1/8	20828	20 1/2	142	313
57	2 1/4	30480	30	225	495

ton = 2240 lb

DIMENSIONS

ROPE DIAMETER		A		B		C		G		N	
mm	in	mm	in	mm	in	mm	in	mm	in	mm	in
26	1	22	7/8	152	6	35	1 3/8	51	2	479	18 7/8
29	1 1/8	22	7/8	171	6 3/4	38	1 1/2	51	2	549	21 5/8
32	1 1/4	26	1	190	7 1/2	41	1 5/8	51	2	622	24 1/2
35	1 3/8	26	1	216	8 1/2	45	1 3/4	64	2 1/2	698	27 1/2
38	1 1/2	29	1 1/8	241	9 1/2	48	1 7/8	64	2 1/2	778	30 5/8
41	1 5/8	29	1 1/8	279	11	51	2	64	2 1/2	867	34 1/8
45	1 3/4	32	1 1/4	317	12 1/2	57	2 1/4	76	3	959	37 3/4
48	1 7/8	32	1 1/4	356	14	57	2 1/4	76	3	1048	41 1/4
51	2	35	1 3/8	394	15 1/2	67	2 5/8	76	3	1140	44 7/8
54	2 1/8	37	1 7/16	432	17	73	2 7/8	89	3 1/2	1230	48 7/16
57	2 1/4	45	1 3/4	470	18 1/2	105	4 1/8	114	4 1/2	1334	52 1/2

